


1. Application

This specification applies to polar Aluminum electrolytic capacitor (foil type) used in electronic equipment.

Designed capacitor's quality meets IEC60384.

2. Part Number System



2.1 Product Type

Code	CBE
Product Type	Radial

2.2 Capacitance code

Code	335	336	337	338
Capacitance (μF)	3.3	33	330	3300

2.3 Rated voltage code

Code	0J	1A	1C	1E	1V	1H	1J
Voltage (WV)	6.3	10	16	25	35	50	63
Code	2A	2C	2D	2E	2V	2G	2W
Voltage (WV)	100	160	200	250	350	400	450

2.4 Capacitance tolerance

Code	M	V
Tolerance Range	±20%	-10%~+20%

2.5 Environmental requirements

Code	R	H
Environmental requirements	ROHS Requirements Remark:Product Set PVC Sleeve	ROHS Requirements and Halogen Free Remark:Product Set PET Sleeve

Issued-date: 2022-11-05

Name

Specification Sheet – CD13D

Revision

B

Page

1

STANDARD MANUAL

2.6 **Products Series Code**

Code	3D
Series	CD13D

2.7 **Diameter**

Code	C	D	E	F	G	J	K	L	M
Diameter	4	5	6.3	8	10	13	16	18	20

2.8 **Case length**

(1) When the code is number, it represent the actual height.(e.g. The code 07 indicates that the height is 7mm; The code 10 indicates that the height is 10mm)

(2) When the code is number + alphabet, please check the following the table:

Code	1A	1B	1C	1D	2A	3A
Case Length(mm)	11.5	12.5	13.5	14.5	21.5	31.5

2.9 **Packaging**

Code	RR	R2	T2	TB	T3	T5
Packaging	Bulk	F8,Lead Pitch=2. 5mm, Bulk	Lead Pitch=2.0mm Taping	Lead Pitch=2.5mm Taping	Lead Pitch=3.5mm Taping	Lead Pitch=5.0mm Taping
Code	T7		CA	CB	CC	CD
Packaging	Lead Pitch=7.5mm Taping		Cutting the feet long=3.0mm	Cutting the feet long=3.5mm	Cutting the feet long=4.0mm	Cutting the feet long=4.5mm

Note: The length of the product's cut feet starts from A=3.0mm. Every time it increases by 0.5mm, the English word is pushed forward one place, as shown in the following table:


Cutting length(mm)	Code
3.0±0.5	CA
3.5±0.5	CB
4.0±0.5	CC
4.5±0.5	CD
5.0±0.5	CE
6.0±0.5	CG
And so on-----	

2.10 **Suffix: Inner Code**

Issued-date: 2022-11-05	Name	Specification Sheet – CD13D		
Revision	B		Page	2
STANDARD MANUAL				

3. Construction:

Single ended type to be produced to fix the terminals to anode and cathode foil, and wind together with paper, and then wound element to be impregnated with electrolyte will be enclosed in an aluminum case. Finally sealed up tightly with end seal rubber, then finished by putting on the vinyl sleeve.



No	Component	Material
1	Lead line	Tinned CP wire (Pb Free)
2	Terminal	Aluminum wire
3	Sealing Material	Rubber
4	Al-Foil (+)	Formed aluminum foil
5	Al-Foil (-)	Etched aluminum foil or formed aluminum foil
6	Case	Aluminum case
7	Sleeve	PET
8	Separator	Electrolyte paper

4. Characteristics

Standard atmospheric conditions

Unless otherwise specified, the standard range of atmospheric conditions for making measurements and tests is as follows:

Ambient temperature	: 15°C to 35°C
Relative humidity	: 45% to 85%
Air Pressure	: 86kPa to 106kPa

If there is any doubt about the results, measurement shall be made within the following conditions:

Ambient temperature	: 20°C ± 2°C
Relative humidity	: 60% to 70%
Air Pressure	: 86kPa to 106kPa

Operating temperature range

The ambient temperature range at which the capacitor can be operated continuously at rated voltage is (10~100WV) -40°C to 125°C, (160~450WV) -25°C to 125°C.

As to the detailed information, please refer to table 1.

Table 1

Item		PERFORMANCE																																				
4.1	Nominal capacitance (Tolerance)	<p><Condition> Measuring Frequency : 120Hz±12Hz Measuring Voltage : Not more than 0.5V Measuring Temperature : 20±2°C</p> <p><Criteria> Shall be within the specified capacitance tolerance.</p>																																				
4.2	Leakage Current	<p><Condition> After DC Voltage is applied to capacitors through the series protective resistor (1kΩ ± 10Ω) so that terminal voltage may reach the reacted use voltage. The leakage current when measured in 2 minutes shall not exceed the values of the following equation.</p> <p><Criteria> 6.3~100V: $I \leq 0.01CV$ or 3 (μA) whichever is greater. 160~450V: $I \leq 0.02CV + 25$ (μA) I: Leakage current (μA) C: Capacitance (μF) V: Rated DC working voltage (V)</p>																																				
4.3	tan δ	<p><Condition> See 4.1 Nominal capacitance, for measuring frequency, voltage and temperature.</p> <p><Criteria></p> <table border="1"> <tr> <td>Working voltage (v)</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>63</td> <td>100</td> </tr> <tr> <td>tan δ(max.)</td> <td>0.20</td> <td>0.16</td> <td>0.14</td> <td>0.12</td> <td>0.10</td> <td>0.19</td> <td>0.15</td> </tr> </table> <table border="1"> <tr> <td>Working voltage (v)</td> <td>160</td> <td>200</td> <td>250</td> <td>350</td> <td>400</td> <td>450</td> </tr> <tr> <td>tan δ(max.)</td> <td>0.15</td> <td>0.15</td> <td>0.15</td> <td>0.20</td> <td>0.20</td> <td>0.20</td> </tr> </table> <p>For capacitance value >1000uF, add 0.02per another 1000uF</p>	Working voltage (v)	10	16	25	35	50	63	100	tan δ(max.)	0.20	0.16	0.14	0.12	0.10	0.19	0.15	Working voltage (v)	160	200	250	350	400	450	tan δ(max.)	0.15	0.15	0.15	0.20	0.20	0.20						
Working voltage (v)	10	16	25	35	50	63	100																															
tan δ(max.)	0.20	0.16	0.14	0.12	0.10	0.19	0.15																															
Working voltage (v)	160	200	250	350	400	450																																
tan δ(max.)	0.15	0.15	0.15	0.20	0.20	0.20																																
4.4	Rated voltage (WV) Surge voltage (SV)	<table border="1"> <tr> <td>WV (V.DC)</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>63</td> <td>100</td> </tr> <tr> <td>SV (V.DC)</td> <td>8.0</td> <td>13</td> <td>20</td> <td>32</td> <td>44</td> <td>63</td> <td>79</td> <td>125</td> </tr> <tr> <td>WV (V.DC)</td> <td>160</td> <td>200</td> <td>250</td> <td>350</td> <td>400</td> <td>450</td> <td></td> <td></td> </tr> <tr> <td>SV (V.DC)</td> <td>200</td> <td>250</td> <td>300</td> <td>400</td> <td>450</td> <td>500</td> <td></td> <td></td> </tr> </table>	WV (V.DC)	6.3	10	16	25	35	50	63	100	SV (V.DC)	8.0	13	20	32	44	63	79	125	WV (V.DC)	160	200	250	350	400	450			SV (V.DC)	200	250	300	400	450	500		
WV (V.DC)	6.3	10	16	25	35	50	63	100																														
SV (V.DC)	8.0	13	20	32	44	63	79	125																														
WV (V.DC)	160	200	250	350	400	450																																
SV (V.DC)	200	250	300	400	450	500																																

4.5 Temperature
characteristic
IEC-60384-4 4.12

<Condition>

STEP	Testing Temperature(°C)	Time
1	20±2	Time to reach thermal equilibrium
2	-40(-25) ±3	Time to reach thermal equilibrium
3	20±2	Time to reach thermal equilibrium
4	125±2	Time to reach thermal equilibrium
5	20±2	Time to reach thermal equilibrium

<Criteria>

- a. At +125°C, capacitance shall be within ±20% of their origin at +20°C, measured capacitance, tan δ shall be within limit of 4.3.
The leakage current value at +105°C shall not more than 8 times the specified value.
- b. At step 5, tan δ shall be within the limit of 4.3.
The leakage current value shall not more than the specified value.
- c. At -40 °C (-25 °C), impedance (Z) ratio shall not exceed the value of the following table.

Rated Voltage (V)	10	16	25~100	160~350	400~420	450
Z-25°C/Z +20°C	3	2	2	4	6	8
Z-40°C/Z +20°C	6	4	4	/	/	/

- d. Capacitance, tan δ, and impedance shall be measured at 120Hz.

4.6 Terminal
Strength
IEC-60384-4 4.4

<Condition>

Tensile strength of terminals
Fixed the capacitor, applied force to the terminal in lead out direction for 10±1 seconds.
Bending strength of terminals
Fixed the capacitor, applied force to bent the terminal (1~4 mm from the rubber) for 90° within 2~3 seconds, and then bent it for 90° to its original position within 2~3 seconds.

Diameter of lead wire	Tensile force N (kgf)	Bending force N (kgf)
0.5mm and less	5 (0.51)	2.5 (0.25)
Over 0.5mm to 0.8mm	10 (1.0)	5 (0.51)

<Criteria>

No noticeable changes shall be found, no breakage or looseness at the terminal.

4.7

Load
Life test
IEC-60384-4 4.13

<Condition>

According to IEC60384-4No.4.13 methods, The capacitor is stored at a temperature of $125\pm 2^{\circ}\text{C}$ with DC bias voltage plus the rated ripple current for $\phi 5\sim\phi 6.3$: 1000+48/0 hours ; $\phi 8\sim\phi 10$: 2000+48/0 hours, $> \phi 10$: 4000+48/0 hours. (The sum of DC and ripple peak voltage shall not exceed the rated working voltage) Then the product should be tested after 16 hours recovering time at atmospheric conditions. The result should meet the following table:

<Criteria>

The characteristic shall meet the following requirements.

Leakage current	Value in 4.2 shall be satisfied
Capacitance Change	Within $\pm 30\%$ of initial value.
tan δ	Not more than 300%of the specified value.
Appearance	There shall be no leakage of electrolyte.

4.8

Shelf
Life test
IEC-60384-4 4.17

<Condition>


The capacitors are then stored with no voltage applied at a temperature of $125\pm 2^{\circ}\text{C}$ for 1000+48/0 hours. Following this period the capacitors shall be removed from the test chamber and be allowed to stabilized at room temperature for 4~8 hours. Next they shall be connected to a series limiting resistor($1k\pm 100\Omega$) with D.C. rated voltage applied for 30min. After which the capacitors shall be discharged, and then, tested the characteristics.

<Criteria>

The characteristic shall meet the following requirements.

Leakage current	Value in 4.2 shall be satisfied
Capacitance Change	Within $\pm 30\%$ of initial value.
tan δ	Not more than 300%of the specified value.
Appearance	There shall be no leakage of electrolyte.

Remark: If the capacitors are stored more than 1 year, the leakage current may increase. Please apply voltage through about $1K\Omega$ resistor, if necessary.

<p>4.9</p>	<p>Surge test IEC-60384-4 4.9</p>	<p><Condition> Test temperature: 15~35°C Series resistor: $R = \frac{100 \pm 50}{C}$ R : protective resistor (K Ω) C : nominal capacitance (μF) Test voltage: Surge voltage item 4.4 No. of cycles: 1000cycles Each cycles lasts for 6±0.5min “ON” for 30±5 s “OFF” for 5±0.5min.</p> <p><Criteria></p> <table border="1"> <tr> <td>Leakage current</td> <td>Not more than the specified value.</td> </tr> <tr> <td>Capacitance Change</td> <td>Within ± 15% of initial value.</td> </tr> <tr> <td>tan δ</td> <td>Not more than the specified value.</td> </tr> <tr> <td>Appearance</td> <td>There shall be no leakage of electrolyte.</td> </tr> </table> <p>Attention: This test simulates over voltage at abnormal situation, and not be hypothesizing that over voltage is always applied.</p>	Leakage current	Not more than the specified value.	Capacitance Change	Within ± 15% of initial value.	tan δ	Not more than the specified value.	Appearance	There shall be no leakage of electrolyte.
Leakage current	Not more than the specified value.									
Capacitance Change	Within ± 15% of initial value.									
tan δ	Not more than the specified value.									
Appearance	There shall be no leakage of electrolyte.									
<p>4.10</p>	<p>Vibration test IEC-60384-4 4.8</p>	<p><Condition> The following conditions shall be applied for 2 hours in each 3 mutually perpendicular directions. Vibration frequency range : 10Hz ~ 55Hz Peak to peak amplitude : 1.5mm Sweep rate : 10Hz ~ 55Hz ~ 10Hz in about 1 minute</p> <p>Mounting method: The capacitor with diameter greater than 12.5mm or longer than 25mm must be fixed in place with a bracket.</p>  <p><Criteria> After the test, the following items shall be tested:</p> <table border="1"> <tr> <td>Inner construction</td> <td>No intermittent contacts, open or short circuiting. No damage of tab terminals or electrodes.</td> </tr> <tr> <td>Appearance</td> <td>No mechanical damage in terminal. No leakage of electrolyte or swelling of the case. The markings shall be legible.</td> </tr> </table>	Inner construction	No intermittent contacts, open or short circuiting. No damage of tab terminals or electrodes.	Appearance	No mechanical damage in terminal. No leakage of electrolyte or swelling of the case. The markings shall be legible.				
Inner construction	No intermittent contacts, open or short circuiting. No damage of tab terminals or electrodes.									
Appearance	No mechanical damage in terminal. No leakage of electrolyte or swelling of the case. The markings shall be legible.									

4.11	Solderability Test IEC-60384-4 4.6	<p><Condition> The capacitor shall be tested under the following conditions: Soldering temperature : 245±3°C Dipping depth : 2mm Dipping speed : 25±2.5mm/s Dipping time : 3±0.5s</p> <p><Criteria></p> <table border="1" data-bbox="563 640 1402 707"> <tr> <td>Coating quality</td> <td>A minimum of 95% of the surface being immersed</td> </tr> </table>	Coating quality	A minimum of 95% of the surface being immersed						
Coating quality	A minimum of 95% of the surface being immersed									
4.12	Resistance to solder heat Test IEC-60384-4 4.5	<p><Condition> Terminals of the capacitor shall be immersed into solder bath at 260±5°C for 10±1seconds or 400±10°C for 3~4 seconds to 1.5~2.0mm from the body of capacitor. Then the capacitor shall be left under the normal temperature and normal humidity for 1~2 hours before measurement.</p> <p><Criteria></p> <table border="1" data-bbox="563 1115 1402 1294"> <tr> <td>Leakage current</td> <td>Not more than the specified value.</td> </tr> <tr> <td>Capacitance Change</td> <td>Within ±10% of initial value.</td> </tr> <tr> <td>tan δ</td> <td>Not more than the specified value.</td> </tr> <tr> <td>Appearance</td> <td>There shall be no leakage of electrolyte.</td> </tr> </table>	Leakage current	Not more than the specified value.	Capacitance Change	Within ±10% of initial value.	tan δ	Not more than the specified value.	Appearance	There shall be no leakage of electrolyte.
Leakage current	Not more than the specified value.									
Capacitance Change	Within ±10% of initial value.									
tan δ	Not more than the specified value.									
Appearance	There shall be no leakage of electrolyte.									
4.13	Damp heat test IEC-60384-4 4.12	<p><Condition> Humidity test: According to IEC60384-4 No.4.12 methods, capacitor shall be exposed for 500±8 hours in an atmosphere of 90~95%R H .at 40±2°C, the characteristic change shall meet the following requirement.</p> <p><Criteria></p> <table border="1" data-bbox="534 1626 1396 1798"> <tr> <td>Leakage current</td> <td>Not more than the specified value.</td> </tr> <tr> <td>Capacitance Change</td> <td>Within ±20% of initial value.</td> </tr> <tr> <td>tan δ</td> <td>Not more than 120% of the specified value.</td> </tr> <tr> <td>Appearance</td> <td>There shall be no leakage of electrolyte.</td> </tr> </table>	Leakage current	Not more than the specified value.	Capacitance Change	Within ±20% of initial value.	tan δ	Not more than 120% of the specified value.	Appearance	There shall be no leakage of electrolyte.
Leakage current	Not more than the specified value.									
Capacitance Change	Within ±20% of initial value.									
tan δ	Not more than 120% of the specified value.									
Appearance	There shall be no leakage of electrolyte.									

4.14

Change of
temperature
Test
IEC-60384-4 4.7

<Condition>

Temperature cycle:

According to IEC60384-4 No.4.7 methods, capacitor shall be placed in an oven, the condition according as below:

Temperature	Time
(1)+20℃	≤3 Minutes
(2) -25℃(-40℃)	30±2 Minutes
(3) +125℃	30±2 Minutes
(1) to (3)=1 cycle, total 5 cycle	

<Criteria>

The characteristic shall meet the following requirement.

Leakage current	Not more than the specified value.
tan δ	Not more than the specified value.
Appearance	There shall be no leakage of electrolyte.

4.15

Vent test
IEC-60384-4 4.16

<Condition>

The following test only apply to those products with vent products at diameter ≥Ø6.3 with vent.

D.C. test

The capacitor is connected with its polarity reversed to a DC power source. Then a current selected from Table 2 is applied.

<Table 2>

Diameter (mm)	DC Current (A)
22.4 or less	1

<Criteria>

The vent shall operate with no dangerous conditions such as flames or dispersion of pieces of the capacitor and/or case.

Issued-date: 2022-11-05

Name

Specification Sheet – CD13D

Revision

B

Page

10

STANDARD MANUAL

5.CASE SIZE & MAX RIPPLE CURRENT

Size Φ D x L(mm) , Maximum Allowable Ripple Current at 125°C,100 kHz (mA)

μ F	WV	10V(1A)		16V(1C)	
	Item	D×L	Ripple Current	D×L	Ripple Current
100				6.3x11	145
330		8x12	360	8x12	360
470		10x12.5	620	10x12.5	620
1000		10x20	960	10x20	960
2200		13x25	1430	13x25	1430
3300		16x25	1900	16x30	2300
4700		16x30	2300	16x35	2550

μ F	WV	25(1E)		35(1V)		50(1H)		63(1J)		100(2A)	
	Item	D×L	Ripple Current	D×L	Ripple Current	D×L	Ripple Current	D×L	Ripple Current	D×L	Ripple Current
4.7						8x12	100			8x12	100
10						8x12	200			8x12	200
22						8x12	260			8x12	220
33						8x12	300	8x12	250	10x12.5	260
47						8x12	300	10x12.5	400	10x16	330
100		8x12	250	8x12	360	10x12.5	520	10x16	450	13x20	670
220		8x12	360	10x12.5	620	10x20	890	13x20	820	16x25	1100
330		10x12.5	620	10x16	800	13x20	1000	13x25	1000	16x30	1300
470		10x16	800	10x20	960	13x25	1200	16x25	1500	18x30	1600
1000		13x20	1100	13x25	1430	16x30	2180	16x30	1850		
2200		16x30	2300	16x35	2550	18x40	2800				
3300		16x35	2550	18x35	2800						

Size Φ D x L(mm) , Maximum Allowable Ripple Current at 125°C,100 kHz (mA)


μ F	WV	200(2D)		250(2E)		350(2V)		400(2G)		450(2W)	
	Item	D×L	Ripple Current	D×L	Ripple Current	D×L	Ripple Current	D×L	Ripple Current	D×L	Ripple Current
1						6.3x11	60	8x12	65	8x12	59
1.8						8x12	75	8x12	75	8x12	68
2.2						8x12	75	8x16	90	8x12	68
3.3						8x16	100	8x16	100	8x16	90
4.7	8x12	120	8x12	120	10x16	125	10x16	125	10x16	10x16	112
5.6	8x12	130	8x16	180	10x16	130	10x16	130	10x16	10x16	115
6.8	8x16	180	8x16	180	10x20	150	10x20	150	10x20	10x20	135
8.2	10x16	200	10x16	200	10x20	168	10x20	168	10x20	10x20	150
10	8x20	240	8x20	240	13x20	186	13x20	186	13x20	13x20	170
15	8x20	240	10x16	240	13x25	226	13x25	226	13x25	13x25	200
22	10x16	240	10x20	260	16x25	283	16x25	283			
33	10x20	320	13x20	350	16x30	375	16x30	375		16x31.5	305
82										18x35.5	600
120								18x30	495		

Remark:

- 1)Specification are subject to change without notice should a safety or technical concern arise regarding the product ,please be sure to contact our sales offices;
- 2)The sizes in the above table are all general specifications; If you need other specifications, please contact us.

6. Dimensions:

Unit: mm



ΦD	5.0	6.3	8(L < 20)	8 (L ≥ 20)	10	12.5/13	16	18	22
F	2.0	2.5	2.5/3.5	3.5	5.0		7.5		10
Φd	0.5			0.6	0.6		0.8		1.0
α	(L < 20) 1.5		(L ≥ 20) 2.0						


7. Multiplier for Ripple Current

Frequency coefficient


Rated Voltage	Coefficient Cap(μF)	Frequency (Hz)			
		120	1k	10k	100k
10~100V	4.7	0.42	0.60	0.80	1.00
	10~33	0.55	0.75	0.90	1.00
	47~330	0.70	0.85	0.95	1.00
	470~1500	0.75	0.90	0.98	1.00
	2200~4700	0.80	0.95	1.00	1.00
200~450V	1~5.6	0.2	0.40	0.80	1.00
	6.8~15	0.3	0.60	0.90	1.00
	22~33	0.5	0.80	0.90	1.00

8. Marking:

Unless otherwise specified. Capacitor shall be clearly marked on its body.

- (1) Brand: Aillen
- (2) Polarity: 
- (3) Nominal capacitance: 470 μ F
- (4) Rated voltage: 63V
- (5) Series: CD13D
- (6) Temperature Range: -40(-25)~+125 $^{\circ}$ C


Casing Type:



Sleeve and printing color: White Printing on black Sleeve.

9. Forming Dimension

Cutting Type



Unit: mm

Shape Code	ϕD	$\phi 5$	$\phi 6.3$	$\phi 8$	$\phi 10 \sim \phi 13$	$\phi 16 \sim \phi 18$
CB Cutting-3.5mm	F	2.0	2.5	3.5	5.0	7.5
	H	3.5	3.5	3.5	3.5	3.5
	d	0.5	0.5	0.5	0.6	0.8

Shape Code	ϕD	$\phi 5$	$\phi 6.3$	$\phi 8$	$\phi 10 \sim \phi 13$	$\phi 16 \sim \phi 18$
CC Cutting-4.0mm	F	2.0	2.5	3.5	5.0	7.5
	H	4.0	4.0	4.0	4.0	4.0
	d	0.5	0.5	0.5	0.6	0.8

Shape Code	ϕD	$\phi 5$	$\phi 6.3$	$\phi 8$	$\phi 10 \sim \phi 13$	$\phi 16 \sim \phi 18$
CD Cutting-4.5mm	F	2.0	2.5	3.5	5.0	7.5
	H	4.5	4.5	4.5	4.5	4.5
	d	0.5	0.5	0.5	0.6	0.8

Shape Code	ϕD	$\phi 5$	$\phi 6.3$	$\phi 8$	$\phi 10 \sim \phi 13$	$\phi 16 \sim \phi 18$
CE Cutting-5.0mm	F	2.0	2.5	3.5	5.0	7.5
	H	5.0	5.0	5.0	5.0	5.0
	d	0.5	0.5	0.5	0.6	0.8

Issued-date: 2022-11-05

Name

Specification Sheet – CD13D

Revision


B

Page

15

10.Taping Dimension:

10.1 Straight foot braid:



Taping dimension

Unit: mm

Code		T2	TB		T3	T5		T7		
Item		Fig1	Fig1		Fig1	Fig1		Fig2		
Taping Code		Fig1	Fig1		Fig1	Fig1		Fig2		
Diameter	ϕD	5	6.3	8	8	10	12.5 &13	12.5 &13	16	18
Height	L	9~30								
Lead Diameter	$\phi d \pm 0.05$	0.5	0.5/0.6		0.5/0.6	0.6	0.6		0.8	
Component Spacing	$P \pm 1.0$	12.7				15.0	25.4	25.4		
Pitch of sprocket holes	$P_0 \pm 0.2$	12.7				15.0	12.7	12.7		
Distance between centers of terminal and the sprocket holes	$P_1 \pm 0.5$	5.10	5.10	4.60	4.60	3.85	3.85	3.85	3.75	
Feed hole center to component center	$P_2 \pm 1.0$	6.35	6.35		6.35	6.35	6.35	6.35	7.50	
Distance between centers of component leads	$F \pm 0.5$	2.0	2.5		3.5	5.0			7.5	
Carrier tape width	$W \pm 1$	18								
Hold down tape width	W_0	7min								
Distance between the center of upper edge of carrier tape and sprocket hole	$W_1 \pm 0.5$	9								
Distance between the upper edges of the carrier tape and the hold down tape	W_2	3max								
Distance between the abscissa and the bottom of the components body	$H \pm 1$	18.5		20.0		18.5				
Distance between the abscissa and the reference plane of ghe components with crimped leads	$H_0 \pm 0.5$	/								
Max. lateral deviation of the component body vertical to the tape plane	Δh	2 max								
End of lead	L_1	0.5Max								
Dia.of driving hole	ϕD_0	4.0 \pm 0.2								
Sun of thickness for mounting and adhesive tape without lead dia	t	0.6 \pm 0.3								

Issued-date: 2022-11-05

Name

Specification Sheet – CD13D

Revision

B

Page

16

10.2 Enlarge the foot braid:

Fig3





Fig4



Taping dimension

Unit: mm

Item	Code	Code														
		TB	T5	TB	T5	TB	T5	T5	T5	T5	T5	T5	T5			
Taping Code		Fig4	Fig3	Fig4	Fig3	Fig4	Fig3	Fig3	Fig3	Fig3			Fig3	Fig3		
Diameter	ϕD	4	5				6.3				8					
Height	L	5&7		5&7		9~12		5&7		9~12		5	7	9~19	20~25	
Lead Diameter	$\phi d \pm 0.05$	0.45				0.50		0.45		0.50		0.45		0.50		0.60
Component Spacing	$P \pm 1.0$	12.7														
Pitch of sprocket holes	$P_0 \pm 0.2$	12.7														
Distance between centers of terminal and the sprocket holes	$P_1 \pm 0.5$	5.1	3.85	5.1	3.85	5.1	3.85	3.85	3.85	3.85	3.85	4.6	4.6	4.6		
Feed hole center to component center	$P_2 \pm 1.0$	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35	6.35		
Distance between centers of component leads	$F \pm 0.5$	2.5	5.0	2.5	5.0	3.5	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0		
Carrier tape width	$W \pm 1$	18														
Hold down tape width	W_0	7min														
Distance between the center of upper edge of carrier tape and sprocket hole	$W_1 \pm 0.5$	9														
Distance between the upper edges of the carrier tape and the hold down tape	W_2	3max														
Distance between the abscissa and the bottom of the components body	$H \pm 0.75$	18.5	17.5	18.5	17.5	18.5	17.5	17.5	17.5	20	20	20	20			
Distance between the abscissa and the reference plane of the components with crimped leads	$H_0 \pm 0.5$	/	16.0	/	16.0	/	16.0	16.0	16.0	16.0	16.0	16.0	16.0			
Max. lateral deviation of the component body vertical to the tape plane	Δh	2 max														
End of lead	L_1	0.5Max														
Dia.of driving hole	ϕD_0	4.0 \pm 0.2														
Sun of thickness for mounting and adhesive tape without lead dia	t	0.6 \pm 0.3														

Issued-date: 2022-11-05

Name

Specification Sheet – CD13D

Revision

B

Page

17

When using Aluminum Electrolytic Capacitors, please pay attention to the points listed below.

If the following types of electrical loads are applied to Aluminum Electrolytic Capacitors, rapid deterioration of electrical property occurs:

- Reverse voltage
- Over voltage exceeding rated working voltage
- Current exceeding rated ripple current
- Severe charging/discharging

At such times, severe heat is generated, gas is emitted, then electrolyte leaks from the sealed area, and pressure relief vent operates due to increase of internal pressure. In the worst case, explosion or ignition may occur, and along with destruction of the capacitor combustibles may burst out.

1. CAUTION DURING CIRCUIT DESIGN

1) OPERATIONAL ENVIRONMENT, MOUNTING ENVIRONMENT AND CONDITIONS

Ensure that operational and mounting conditions follow the specified conditions detailed in the catalog and specification sheets

2) OPERATING TEMPERATURE, RIPPLE CURRENT AND LOAD LIFE.

Operating temperature and applied ripple current should be within the specified value in the catalog or specification sheets.

Do not use Aluminum Electrolytic Capacitors at temperature which exceeds the specified category temperatures range.

Do not apply excessive current to the capacitors, which exceeds the specified rated ripple current.

During circuit design, please ensure that capacitors are selected to match with the lifetime requirements of the application

3) APPLICATION

Aluminum Electrolytic Capacitors are normally polarized. Reverse voltage or AC voltage should not be applied. When polarity may flip over, non-polar type should be used, but the non-polar type cannot be used for AC.

Standard Aluminum Electrolytic Capacitors are not suitable for rapid charge and discharge applications. Please consult with Shanghai Suzuki Electronics or sales office of Suzuki Techno Group in your area about special designed capacitors for rapid charge and discharge.

4) APPLIED VOLTAGE

Do not exceed the rated voltage of capacitors

5) INSULATION

Aluminum Electrolytic Capacitors should be electrically isolated from the following.

Aluminum case, cathode lead wire, anode lead wire and circuit pattern;

Auxiliary terminals of snap-in type, anode terminal, outward terminals and circuit pattern.

The PVC sleeve of Aluminum Electrolytic Capacitors is not recognized as an insulator, and therefore, the standard capacitor should not be used in a place where insulation function is needed.

Issued-date: 2022-11-05

Name

Specification Sheet – CD13D

Revision

B

Page

18

Please consult with Shanghai Suzuki Electronics or sales office of Suzuki Techno Group in your area, if you require a higher grade of insulating sleeve.

6) CONDITIONS OF USE

The following environments should be avoided when using Aluminum Electrolytic Capacitors.

Damp conditions such as water, salt water or oil spray or fumes, high humidity or humidity condensation situations;

Hazardous gas/fumes such as hydrogen sulfide, sulfurous acid gas, nitrous acid, chlorine gas, ammonia or bromine gas;

Exposure of ozone, ultraviolet rays or radiation;

Severe vibration or shock which exceeds the condition specified in the catalog or specification sheets.

7) CONSIDERATION TO ASSEMBLY CONDITION

In designing a circuit, the following matters should be ensured in advance to the capacitor's assembly on the printed circuit board (PC board)

Design the appropriate hole spacing to match the lead pitch of capacitors;

Do not locate any wiring and circuit patterns directly above the capacitor's vent;

Ensure enough free space above the capacitor's vent. The recommended space is specified in the catalog or specification sheets;

In case the capacitor's vent is facing the PC board, make a gas release hole on PC board.

The sealing side of the screw terminal type should not face down in the application. When the capacitors are mounted horizontally, the anode screw terminals must be positioned at upper side.

8) CONSIDERATION TO CIRCUIT DESIGN

Any copper lines or circuit patterns should not be laid under the capacitor;

Parts which radiate heat should not be placed close to the reverse side of the Aluminum Electrolytic Capacitors on the PC board.

9) OTHERS

Performance of electrical characteristics of Aluminum Electrolytic Capacitors is affected by variation of operating temperature and frequency. Consider this variation when designing the circuit.

Excessive holes and connection hole between both sides on the PC board should be avoided around or under the mounting area of the Aluminum Electrolytic Capacitors on double sided or multilayer PC board.

Torque of tightening screw terminals should not exceed the specified maximum value which is described in the catalog and specification sheets.

Consider current balance when 2 or more Aluminum Electrolytic Capacitors are connected in parallel.

Use bleeder resistors when 2 or more Aluminum Electrolytic Capacitors are connected in series. In this case, the resistors should be connected parallel to the capacitors.

2. CAUTION FOR ASSEMBLING CAPACITORS

1) CAUTION BEFORE ASSEMBLY

Aluminum Electrolytic Capacitors cannot be recycled after mounting and applying electricity in unit. The capacitors, which are removed from PC board for the purpose of measuring electrical characteristics at the periodical inspection, should only be recycled for the same position.;

Aluminum Electrolytic Capacitors may accumulate charge naturally during storage. In this case, discharge through a 1KOHM resistor before use;

Leakage current of Aluminum Electrolytic Capacitors may be increased during long storage time. In this case, the capacitors should be subject to voltage treatment through a 1KOHM resistor before use.

2) IN THE ASSEMBLY PROCESS-1

Ensure rated voltage and capacitance of the capacitors before mounting;

Ensure capacitors polarity before mounting;

Do not use a capacitor which has been dropped onto a hard surface;

Do not use a capacitor with damaged or dented cases or seals.

3) IN THE ASSEMBLY PROCESS-2

Capacitors should be mounted after confirmation that hole spacing on PC board matches the lead pitch of the capacitors;

The snap-in type of capacitors should be mounted firmly on the PC board without a gap between the capacitor body and the surface of PC board.;

Avoid excessive force when clinching lead wire during auto-insertion process;

Avoid excessive shock to capacitors by automatic inserting machine, during mounting, parts inspection or centering operations;

Please utilize supporting material such as strap of adhesive to mount capacitors to PC board when it is anticipated that vibration or shock is applied.

4) SOLDERING

Soldering conditions (temperature, time) should be within the specified conditions which are described in the catalog or specification sheets;

In case lead wire reforming is needed due to inappropriate pitch between capacitor and holes on PC board, stress to the capacitor should be avoided;

In case of maintenance by soldering iron, if it is required to detach the capacitor, it should be removed from PC board after solder has melted sufficiently in order to reduce stress on the lead wires/terminals of the capacitor;

Soldering iron should never touch the capacitor's body.

5) FLOW SOLDERING

Do not dip capacitor's body into melted solder,.It should only be soldered on the reverse side of the PC board on which the capacitors are mounted;

Soldering condition((preheat,soldering temperature,dipping time)should be within the specified standard which is described in the catalog or specification sheets;

Flux should not be adhered to capacitor's body but only to its terminals;

Other devices which are mounted close to capacitors should not touch the capacitors.

6) REFLOW SOLDERING

Reflow soldering conditions(preheat,soldering,temperature,reflow time)should follow the specified standard which is described in the catalog or specification sheets;

Heating standard should depend on surface of the capacitor color or materials when infrared rays are used because the capacitor's heat absorption depends on the surface color or materials.Check heat condition;

Standard Aluminum Electrolytic Capacitors cannot withstand two or more reflow processes.

7) HANDLING AFTER SOLDERING

Do not bend or twist the capacitor's body after soldering on PC board;

Do not pick-up or move PC board by holding the soldered capacitors;

Do not hit the capacitors and isolate capacitors from the PC board or other device when stacking PC boards in store.

8) PC BOARD CLEANING

Standard Aluminum Electrolytic Capacitors should be free from halogenated solvents during PC board cleaning after soldering.

9) ADHESIVES AND COATING MATERIALS

Do not use halogenated adhesives and coating materials to fix Aluminum Electrolytic Capacitors;

Flux between the surface of the PC board and sealing of capacitors should be cleaned before using adhesives or coating materials;

Solvents should be dried up before using adhesives or coating materials;

Do not cover up all the sealing area of capacitors with adhesives or coating materials,make coverage only partial.

3. CAUTION DURING USE OF CAPACITORS IN SETS

- 3.1 Do not touch the terminals of capacitors;
- 3.2 Do not connect electrical terminals of the capacitors.Keep the capacitors free from conductive solution,such as acid,alkali and so on;
- 3.3 Ensure the operational environment of the equipment in which the capacitor has been built is within the specified condition mentioned in the catalog or specification sheets.

4. MAINTENANCE

- 4.1 Periodical inspection should be carried out for the capacitors,which are used with industrial equipment; Check the following points at the inspection.
- 4.2 Visual inspection to check pressure relief vent open or leakage of electrolyte;
- 4.3 Electrical characteristics:leakage current,capacitance,dissipation factor and the other points which are mentioned in the catalog or specification sheets.

5. EMERGENCY ACTION

- 5.1 If the pressure relief vent is open and some gas blows out from the capacitor,turn the main switch of the equipment off or pull out the plug from the power outlet immediately;
- 5.2 During pressure relief vent operation,extremely hot gas(over 100°C)may blow out from the vent area of the capacitors.So keep your face and skin away from capacitors during its operation.In case of eye contact,flush the open eye(s)with large amount of clean water immediately.In case of ingestion,gargle with water immediately,and do not swallow.Also do not touch elctrolyte but wash skin with soap and water in case of skin contact.

6. STORAGE CONDITIO

- 6.1 Aluminum Electrolytic Capacitors should not be stored in high temperature or in high humidity.The suitable storage condition is 5°C-35°C,and less than 75% in relative humidity;
- 6.2 Aluminum Electrolytic Capacitors should not be stored in damp conditions such as water,salt water spray or oil spray;
- 6.3 Do not store Aluminum Electrolytic Capacitors in an environment full of hazardous gas (hydrogen sulfide gas,sulfurous acid gas,nitrous acid,chlorine gas,ammonia or btomine gas);
- 6.4 Aluminum Electrolytic Capacitors should not be stored under exposure to ozone ,ultraviolet rays or radiation.
- 6.5 After one year, a capacitor should be reconditioned by applying rated voltage in series with a 1000Ω current limiting resistor for a time period of 30 minutes.

7. DISPOSAL

- 1)Please take either of the following actions in case of disposal.
Incinerarion (high temperature of more than 800°C)after crushing the capacitor's body;
- 2)Consignment to specialists of industrial waste.

Issued-date: 2022-11-05	Name	Specification Sheet – CD13D		
Revision	B	Page	22	
STANDARD MANUAL				