

发行日期: \_\_\_\_\_

承认书编号: \_\_\_\_\_

# 承认书

## Approval Sheet

客户名称 Customer :

爱伦料号 Aillen P/N :

CDEP Series

规格描述 Description :


客户料号 Customer P/N :

客户接收

接收日期: \_\_\_\_\_

| 接收者 | 检验者 | 确认 | 审核 | 客户盖章 |
|-----|-----|----|----|------|
|     |     |    |    |      |

供应商

| 编制  | 确认 | 审核 | 公司盖章  |
|-----|----|----|---|
| 常斯琴 | /  | 彭旭 |  |

爱 伦 电 子 科 技 有 限 公 司

**Aillen Electronic Technology Limited**

香港:香港湾仔庄士敦道 181 号大有大厦 10 楼 1001 室

ADD:1001R.10F Taiyau Building.181 Johnston Road.Wanchai H.K

TEL: 00852-36458129 FAX: 00852-36458092

东莞:广东省东莞市东城区东莞大道 11 号环球经贸中心 A805

ADD:A805 TBA Tower NO. 11 DongGuan Road ,DongGuan,GuangDong

TEL: 0769-23124124 /88050188 FAX: 0769-23124135

<http://www.aillen.com>E-mail: [skychung@aillen.com](mailto:skychung@aillen.com)


## ALTERNATION HISTORY RECORDS 变更记录

| Date<br>日期 | Version<br>版本 | Mark<br>标记 | Page<br>页码 | Description<br>描述 | Drafter<br>制定者 | Approver<br>审批者 |
|------------|---------------|------------|------------|-------------------|----------------|-----------------|
| 2019-05-25 | A             | /          | 20         | 首次发行              | 常斯琴            | 彭旭              |
|            |               |            |            |                   |                |                 |

## 1. Application

This specification applies to polar Aluminum electrolytic capacitor (foil type) used in electronic equipment. Designed capacitor's quality meets IEC60384.

## 2. Part Number System



### 2.1 Product Type:

| Code         | CSE     |
|--------------|---------|
| Product Type | Snap-in |

### 2.2 Capacitance code

| Code             | 686 | 827 | 688  |
|------------------|-----|-----|------|
| Capacitance (μF) | 68  | 820 | 6800 |

### 2.3 Capacitance tolerance

| Code            | M    | K    | V         | Q         | R      |
|-----------------|------|------|-----------|-----------|--------|
| Tolerance Range | ±20% | ±10% | -10%~+20% | -10%~+30% | 0~+20% |

### 2.4 Rated voltage code

| Code           | 1A | 1C | 1E | 1V | 1H | 1K | 2A  | 2C  | 2E  | 2R  | 2V  | 2G  | 2W  |
|----------------|----|----|----|----|----|----|-----|-----|-----|-----|-----|-----|-----|
| Voltage (W.V.) | 10 | 16 | 25 | 35 | 50 | 80 | 100 | 160 | 250 | 315 | 350 | 400 | 450 |

### 2.5 Environmental requirements

| Code                       | R                 | H               |
|----------------------------|-------------------|-----------------|
| Environmental requirements | ROHS Requirements | HF Requirements |

### 2.6 Products Series Code:

| Code   | CD293 | CD294 | CDKP | CDEP |
|--------|-------|-------|------|------|
| Series | 93    | 94    | KP   | EP   |

### 2.7 Diameter

| Code     | M  | N  | O  | P  | Q  |
|----------|----|----|----|----|----|
| Diameter | 20 | 22 | 25 | 30 | 35 |

### 2.8 Case length

| Code       | 25 | 2J   | 30 | 3A   | 35 | 3E   |
|------------|----|------|----|------|----|------|
| length(mm) | 25 | 29.5 | 30 | 31.5 | 35 | 35.5 |


### 2.9 Type

| Code | SW     | SZ      |
|------|--------|---------|
| Type | W-Type | Z- Type |

### 2.10 “\*” indicates production line.

### 3. Construction

Single ended type to be produced to fix the terminals to anode and cathode foil, and wind together with paper, and then wound element to be impregnated with electrolyte will be enclosed in an aluminum case. Finally sealed up tightly with end seal rubber, then finished by putting on the vinyl sleeve.



| No | Component | Material                          |
|----|-----------|-----------------------------------|
| 1  | Case      | Aluminum case                     |
| 2  | Sleeve    | PET                               |
| 3  | Terminal  | Solder coated copper clad steel   |
| 4  | Seal      | Rubber-laminated bakelite         |
| 5  | Rivet     | Aluminum                          |
| 6  | Washer    | Aluminum                          |
| 7  | Tab       | Aluminum                          |
| 8  | Element   | Aluminum foil & Electrolyte paper |

#### 4. Characteristics

##### Standard atmospheric conditions

Unless otherwise specified, the standard range of atmospheric conditions for making measurements and tests is as follows:

Ambient temperature : 15°C to 35°C

Relative humidity : 45% to 85%

Air Pressure : 86kPa to 106kPa

If there is any doubt about the results, measurement shall be made within the following conditions:

Ambient temperature : 20°C ± 2°C

Relative humidity : 60% to 70%

Air Pressure : 86kPa to 106kPa

##### Operating temperature range

The ambient temperature range at which the capacitor can be operated continuously at rated voltage is (10~100WV) -40°C to 105°C or (160~450WV) -25°C to 105°C.

As to the detailed information, please refer to table 1


Table 1

| ITEM                |                                      | PERFORMANCE  |      |      |      |      |      |      |     |     |                     |    |    |    |    |    |    |    |     |              |      |      |      |      |      |      |      |      |                     |     |     |     |     |     |     |              |      |      |      |      |      |      |
|---------------------|--------------------------------------|--|------|------|------|------|------|------|-----|-----|---------------------|----|----|----|----|----|----|----|-----|--------------|------|------|------|------|------|------|------|------|---------------------|-----|-----|-----|-----|-----|-----|--------------|------|------|------|------|------|------|
| 4.1                 | Rated Voltage (WV)                   | WV (V.DC)  | 10   | 16   | 25   | 35   | 50   | 63   | 80  | 100 |                     |    |    |    |    |    |    |    |     |              |      |      |      |      |      |      |      |      |                     |     |     |     |     |     |     |              |      |      |      |      |      |      |
|                     |                                      | SV (V.DC)  | 13   | 20   | 32   | 44   | 63   | 79   | 100 | 125 |                     |    |    |    |    |    |    |    |     |              |      |      |      |      |      |      |      |      |                     |     |     |     |     |     |     |              |      |      |      |      |      |      |
|                     | Surge Voltage (SV)                   | WV (V.DC)  | 160  | 180  | 200  | 250  | 315  | 350  | 400 | 450 |                     |    |    |    |    |    |    |    |     |              |      |      |      |      |      |      |      |      |                     |     |     |     |     |     |     |              |      |      |      |      |      |      |
|                     |                                      | SV (V.DC)  | 200  | 220  | 250  | 300  | 365  | 400  | 450 | 500 |                     |    |    |    |    |    |    |    |     |              |      |      |      |      |      |      |      |      |                     |     |     |     |     |     |     |              |      |      |      |      |      |      |
| 4.2                 | Nominal capacitance (Tolerance) ±20% | <b>&lt;Condition&gt;</b><br>Measuring Frequency : 120Hz±12Hz<br>Measuring Voltage : Not more than 0.5Vrms<br>Measuring Temperature : 20±2℃<br><b>&lt;Criteria&gt;</b><br>Shall be within the specified capacitance tolerance.  |      |      |      |      |      |      |     |     |                     |    |    |    |    |    |    |    |     |              |      |      |      |      |      |      |      |      |                     |     |     |     |     |     |     |              |      |      |      |      |      |      |
| 4.3                 | Leakage current                      | <b>&lt;Condition&gt;</b><br>Connecting the capacitor with a protective resistor (1k Ω ± 10 Ω ) in series for 5 minutes, and then, measure leakage current.<br><b>&lt;Criteria&gt;</b><br>I≤3√CV ( μ A)<br>I: Leakage current ( μ A)<br>C: Capacitance ( μ F)<br>V: Rated DC working voltage (V)  |      |      |      |      |      |      |     |     |                     |    |    |    |    |    |    |    |     |              |      |      |      |      |      |      |      |      |                     |     |     |     |     |     |     |              |      |      |      |      |      |      |
| 4.4                 | tan δ                                | <b>&lt;Condition&gt;</b><br>See 4.2 Nominal capacitance, for measuring frequency, voltage and temperature.<br><b>&lt;Criteria&gt;</b> <table><tr><td>Working voltage (v)</td><td>10</td><td>16</td><td>25</td><td>35</td><td>50</td><td>63</td><td>80</td><td>100</td></tr><tr><td>tan δ (max.)</td><td>0.60</td><td>0.45</td><td>0.30</td><td>0.25</td><td>0.20</td><td>0.15</td><td>0.15</td><td>0.15</td></tr></table><br><table><tr><td>Working voltage (v)</td><td>160</td><td>200</td><td>250</td><td>350</td><td>400</td><td>450</td></tr><tr><td>tan δ (max.)</td><td>0.15</td><td>0.15</td><td>0.15</td><td>0.15</td><td>0.15</td><td>0.20</td></tr></table><br>For capacitance value >1000uF, add 0.02per another 1000uF |      |      |      |      |      |      |     |     | Working voltage (v) | 10 | 16 | 25 | 35 | 50 | 63 | 80 | 100 | tan δ (max.) | 0.60 | 0.45 | 0.30 | 0.25 | 0.20 | 0.15 | 0.15 | 0.15 | Working voltage (v) | 160 | 200 | 250 | 350 | 400 | 450 | tan δ (max.) | 0.15 | 0.15 | 0.15 | 0.15 | 0.15 | 0.20 |
| Working voltage (v) | 10                                   | 16   | 25   | 35   | 50   | 63   | 80   | 100  |     |     |                     |    |    |    |    |    |    |    |     |              |      |      |      |      |      |      |      |      |                     |     |     |     |     |     |     |              |      |      |      |      |      |      |
| tan δ (max.)        | 0.60                                 | 0.45   | 0.30 | 0.25 | 0.20 | 0.15 | 0.15 | 0.15 |     |     |                     |    |    |    |    |    |    |    |     |              |      |      |      |      |      |      |      |      |                     |     |     |     |     |     |     |              |      |      |      |      |      |      |
| Working voltage (v) | 160                                  | 200  | 250  | 350  | 400  | 450  |      |      |     |     |                     |    |    |    |    |    |    |    |     |              |      |      |      |      |      |      |      |      |                     |     |     |     |     |     |     |              |      |      |      |      |      |      |
| tan δ (max.)        | 0.15                                 | 0.15   | 0.15 | 0.15 | 0.15 | 0.20 |      |      |     |     |                     |    |    |    |    |    |    |    |     |              |      |      |      |      |      |      |      |      |                     |     |     |     |     |     |     |              |      |      |      |      |      |      |
| 4.5                 | Terminal strength                    | <b>&lt;Condition&gt;</b><br>A static load of 25N (2.5kgf) shall be applied to the lead wire terminal in the axial direction away from the capacitor body for 30s.<br><b>&lt;Criteria&gt;</b><br>There shall be no intermittent contacts, open or short circuit and there shall be no mechanical damage such as terminal damage.  |      |      |      |      |      |      |     |     |                     |    |    |    |    |    |    |    |     |              |      |      |      |      |      |      |      |      |                     |     |     |     |     |     |     |              |      |      |      |      |      |      |

| 4.6   | Temperature characteristics               | <b>&lt;Condition&gt;</b>  | <table><tr><th>STEP</th><th>Testing Temperature(°C)</th><th>Time</th></tr><tr><td>1</td><td>20±2</td><td>Time to reach thermal equilibrium</td></tr><tr><td>2</td><td>-40±3/-25±3</td><td>Time to reach thermal equilibrium</td></tr><tr><td>3</td><td>20±2</td><td>Time to reach thermal equilibrium</td></tr><tr><td>4</td><td>105±2</td><td>Time to reach thermal equilibrium</td></tr><tr><td>5</td><td>20±2</td><td>Time to reach thermal equilibrium</td></tr></table> | STEP                              | Testing Temperature(°C) | Time                          | 1             | 20±2                                      | Time to reach thermal equilibrium | 2   | -40±3/-25±3   | Time to reach thermal equilibrium | 3 | 20±2 | Time to reach thermal equilibrium | 4 | 105±2 | Time to reach thermal equilibrium | 5 | 20±2 | Time to reach thermal equilibrium |
|---|---|---|--|-----------------------------------|-------------------------|-------------------------------|---------------|---|-----------------------------------|---|---------------|-----------------------------------|---|------|-----------------------------------|---|-------|-----------------------------------|---|------|-----------------------------------|
|   |   | STEP  | Testing Temperature(°C)  | Time                              |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   | 1   | 20±2   | Time to reach thermal equilibrium |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   | 2   | -40±3/-25±3  | Time to reach thermal equilibrium |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   | 3   | 20±2   | Time to reach thermal equilibrium |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   | 4   | 105±2  | Time to reach thermal equilibrium |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   | 5   | 20±2   | Time to reach thermal equilibrium |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   | <b>&lt;Criteria&gt;</b>   | <p>a. At +105℃, capacitance measured shall be within ±20% of its original value at +20℃.</p> <p>tan δ shall be within the limit of Item 4.4</p> <p>The leakage current measured shall not more than 8 times of its specified value.</p> <p>b. In step 5, tan δ shall be within the limit of Item 4.4</p> <p>The leakage current shall not more than the specified value.</p> <p>c. At-40℃/-25℃, Impedance (Z) ratio shall not exceed the value of the following table.</p>   |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   | <table><tr><td>Rated Voltage (V)</td><td>10~100</td><td>160~250</td><td>350~500</td></tr><tr><td>Z-25℃/ Z +20℃</td><td>6</td><td>8</td><td>8</td></tr><tr><td>Z-40℃/ Z +20℃</td><td>20</td><td>/</td><td>/</td></tr></table>  | Rated Voltage (V)  | 10~100                            | 160~250                 | 350~500                       | Z-25℃/ Z +20℃ | 6   | 8                                 | 8   | Z-40℃/ Z +20℃ | 20                                | / | /    |                                   |   |       |                                   |   |      |                                   |
|   |   | Rated Voltage (V)   | 10~100   | 160~250                           | 350~500                 |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
| Z-25℃/ Z +20℃   | 6   | 8   | 8  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
| Z-40℃/ Z +20℃   | 20  | /   | /  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
| Capacitance, tan δ, and impedance shall be measured at 120Hz. |   |   |  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   |   |  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   |   |  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   |   |  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   |   |  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   |   |  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
| 4.7   | Load life test                            | <b>&lt;Condition&gt;</b>  | According to IEC60384-4No.4.13 methods, The capacitor is stored at a temperature of 105±2℃ with DC bias voltage plus the rated ripple current for 5000+48/0 hours. (The sum of DC and ripple peak voltage shall not exceed the rated working voltage) Then the product should be tested after 16 hours recovering time at atmospheric conditions. The result should meet the following table:  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   | <b>&lt;Criteria&gt;</b>   | The characteristic shall meet the following requirements.  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   | <table><tr><td>Leakage current</td><td>Value in 4.3 shall be satisfied</td></tr><tr><td>Capacitance Change</td><td>Within ±20% of initial value.</td></tr><tr><td>tan δ</td><td>Not more than 200%of the specified value.</td></tr><tr><td>Appearance</td><td>There shall be no leakage of electrolyte.</td></tr></table> | Leakage current  | Value in 4.3 shall be satisfied   | Capacitance Change      | Within ±20% of initial value. | tan δ         | Not more than 200%of the specified value. | Appearance                        | There shall be no leakage of electrolyte. |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   | Leakage current   | Value in 4.3 shall be satisfied  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   | Capacitance Change  | Within ±20% of initial value.  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   | tan δ   | Not more than 200%of the specified value.  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
| Appearance  | There shall be no leakage of electrolyte. |   |  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   |   |  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   |   |  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |
|   |   |   |  |                                   |                         |                               |               |   |                                   |   |               |                                   |   |      |                                   |   |       |                                   |   |      |                                   |

|                    |  |  |                 |  |                    |                               |       |   |            |   |
|--------------------|--|--|-----------------|--|--------------------|-------------------------------|-------|---|------------|---|
| 4.8                | Shelf life test                                | <p><b>&lt;Condition&gt;</b><br/>The capacitors are then stored with no voltage applied at a temperature of 105±2°C for 1000+48/0 hours. Following this period the capacitors shall be removed from the test chamber and be allowed to stabilized at room temperature for 4~8 hours. Next they shall be connected to a series limiting resistor(1k±100Ω) with D.C. rated voltage applied for 30min. After which the capacitors shall be discharged, and then, tested the characteristics.</p> <p><b>&lt;Criteria&gt;</b><br/>The characteristic shall meet the following requirements.</p> <table><tr><td>Leakage current</td><td>Value in 4.3 shall be satisfied</td></tr><tr><td>Capacitance Change</td><td>Within ±15% of initial value.</td></tr><tr><td>tan δ</td><td>Not more than 150%of the specified value.</td></tr><tr><td>Appearance</td><td>There shall be no leakage of electrolyte.</td></tr></table> <p>Remark: If the capacitors are stored more than 1 year, the leakage current may increase. Please apply voltage through about 1 K Ω resistor, if necessary.</p> | Leakage current | Value in 4.3 shall be satisfied                | Capacitance Change | Within ±15% of initial value. | tan δ | Not more than 150%of the specified value. | Appearance | There shall be no leakage of electrolyte. |
| Leakage current    | Value in 4.3 shall be satisfied                |  |                 |  |                    |                               |       |   |            |   |
| Capacitance Change | Within ±15% of initial value.                  |  |                 |  |                    |                               |       |   |            |   |
| tan δ              | Not more than 150%of the specified value.      |  |                 |  |                    |                               |       |   |            |   |
| Appearance         | There shall be no leakage of electrolyte.      |  |                 |  |                    |                               |       |   |            |   |
| 4.9                | Surge test                                     | <p><b>&lt;Condition&gt;</b><br/>Applied a surge voltage to the capacitor connected with a (100 ±50)/CR (KΩ) resistor.<br/>The capacitor shall be submitted to 1000 cycles, each consisting of charge of 30 ±5s, followed discharge of 5 min 30s.<br/>The test temperature shall be 15~35°C.<br/>C<sub>R</sub> :Nominal Capacitance ( μ F)</p> <p><b>&lt;Criteria&gt;</b></p> <table><tr><td>Leakage current</td><td>Not more than the specified value.</td></tr><tr><td>Capacitance Change</td><td>Within ±15% of initial value.</td></tr><tr><td>tan δ</td><td>Not more than the specified value.</td></tr><tr><td>Appearance</td><td>There shall be no leakage of electrolyte.</td></tr></table> <p>Attention:<br/>This test simulates over voltage at abnormal situation only.<br/>It is not applicable to such over voltage as often applied.</p>  | Leakage current | Not more than the specified value.             | Capacitance Change | Within ±15% of initial value. | tan δ | Not more than the specified value.        | Appearance | There shall be no leakage of electrolyte. |
| Leakage current    | Not more than the specified value.             |  |                 |  |                    |                               |       |   |            |   |
| Capacitance Change | Within ±15% of initial value.                  |  |                 |  |                    |                               |       |   |            |   |
| tan δ              | Not more than the specified value.             |  |                 |  |                    |                               |       |   |            |   |
| Appearance         | There shall be no leakage of electrolyte.      |  |                 |  |                    |                               |       |   |            |   |
| 4.10               | Solderability test                             | <p><b>&lt;Condition&gt;</b><br/>The capacitor shall be tested under the following conditions:<br/>Soldering temperature : 245±3°C<br/>Dipping depth : 2mm<br/>Dipping speed : 25±2.5mm/s<br/>Dipping time : 3±0.5s</p> <p><b>&lt;Criteria&gt;</b></p> <table><tr><td>Coating quality</td><td>A minimum of 95% of the surface being immersed</td></tr></table>  | Coating quality | A minimum of 95% of the surface being immersed |                    |                               |       |   |            |   |
| Coating quality    | A minimum of 95% of the surface being immersed |  |                 |  |                    |                               |       |   |            |   |



|                    |   |   |                    |  |                    |   |               |                                    |            |   |
|--------------------|---|---|--------------------|--|--------------------|---|---------------|------------------------------------|------------|---|
| 4.11               | Vibration test  | <p><b>&lt;Condition&gt;</b></p> <p>The following conditions shall be applied for 2 hours in each 3 mutually perpendicular directions.</p> <p>Vibration frequency range : 10Hz ~ 55Hz</p> <p>Peak to peak amplitude : 1.5mm</p> <p>Sweep rate : 10Hz ~ 55Hz ~ 10Hz in about 1 minute</p> <p><b>&lt;Criteria&gt;</b></p> <p>After the test, the following items shall be tested:</p> <table><tr><td>Inner construction</td><td>No intermittent contact, open or short circuit.<br/>No damage of tab terminals or electrodes.</td></tr><tr><td>Appearance</td><td>No mechanical damage in terminal. No leakage of electrolyte or swelling of the case. The markings shall be legible.</td></tr></table> <p>Mounting method: The capacitor must be fixed in place with a bracket.</p>  | Inner construction | No intermittent contact, open or short circuit.<br>No damage of tab terminals or electrodes. | Appearance         | No mechanical damage in terminal. No leakage of electrolyte or swelling of the case. The markings shall be legible. |               |                                    |            |   |
| Inner construction | No intermittent contact, open or short circuit.<br>No damage of tab terminals or electrodes.                        |   |                    |  |                    |   |               |                                    |            |   |
| Appearance         | No mechanical damage in terminal. No leakage of electrolyte or swelling of the case. The markings shall be legible. |   |                    |  |                    |   |               |                                    |            |   |
| 4.12               | Resistance to solder heat test  | <p><b>&lt;Condition&gt;</b></p> <p>Terminals of the capacitor shall be immersed into solder bath at <math>260 \pm 5^{\circ}\text{C}</math> for <math>10 \pm 1</math>seconds or <math>400 \pm 10^{\circ}\text{C}</math> fo for <math>3^{+1}_{-0}</math> seconds to 1.5~2.0mm from the body of capacitor.</p> <p>Then the capacitor shall be left under the normal temperature and normal humidity for 1~2 hours before measurement.</p> <p><b>&lt;Criteria&gt;</b></p> <table><tr><td>Leakage current</td><td>Not more than the specified value.</td></tr><tr><td>Capacitance Change</td><td>Within <math>\pm 10\%</math> of initial value.</td></tr><tr><td><math>\tan \delta</math></td><td>Not more than the specified value.</td></tr><tr><td>Appearance</td><td>There shall be no leakage of electrolyte.</td></tr></table>                                       | Leakage current    | Not more than the specified value.   | Capacitance Change | Within $\pm 10\%$ of initial value.   | $\tan \delta$ | Not more than the specified value. | Appearance | There shall be no leakage of electrolyte. |
| Leakage current    | Not more than the specified value.  |   |                    |  |                    |   |               |                                    |            |   |
| Capacitance Change | Within $\pm 10\%$ of initial value.   |   |                    |  |                    |   |               |                                    |            |   |
| $\tan \delta$      | Not more than the specified value.  |   |                    |  |                    |   |               |                                    |            |   |
| Appearance         | There shall be no leakage of electrolyte.   |   |                    |  |                    |   |               |                                    |            |   |

| 4.13                              | Change of temperature test                 | <p>&lt;Condition&gt;<br/>Temperature cycle:<br/>According to IEC60384-4 No.4.7 methods, capacitor shall be placed in an oven, the condition according as below:</p> <table><tr><th>Temperature</th><th>Time</th></tr><tr><td>(1)+20℃</td><td>≤3 Minutes</td></tr><tr><td>(2) -25℃(-40℃)</td><td>30±2 Minutes</td></tr><tr><td>(3) +105℃</td><td>30±2 Minutes</td></tr><tr><td colspan="2">(1) to (3)=1 cycle, total 5 cycle</td></tr></table> <p>&lt;Criteria&gt;<br/>The characteristic shall meet the following requirement.</p> <table><tr><td>Leakage current</td><td>Not more than the specified value.</td></tr><tr><td>tan δ</td><td>Not more than the specified value.</td></tr><tr><td>Appearance</td><td>There shall be no leakage of electrolyte.</td></tr></table> | Temperature     | Time                               | (1)+20℃            | ≤3 Minutes                    | (2) -25℃(-40℃) | 30±2 Minutes                               | (3) +105℃  | 30±2 Minutes                              | (1) to (3)=1 cycle, total 5 cycle |  | Leakage current | Not more than the specified value. | tan δ | Not more than the specified value. | Appearance | There shall be no leakage of electrolyte. |
|-----------------------------------|--|--|-----------------|------------------------------------|--------------------|-------------------------------|----------------|--|------------|---|-----------------------------------|--|-----------------|------------------------------------|-------|------------------------------------|------------|---|
| Temperature                       | Time                                       |  |                 |                                    |                    |                               |                |  |            |   |                                   |  |                 |                                    |       |                                    |            |   |
| (1)+20℃                           | ≤3 Minutes                                 |  |                 |                                    |                    |                               |                |  |            |   |                                   |  |                 |                                    |       |                                    |            |   |
| (2) -25℃(-40℃)                    | 30±2 Minutes                               |  |                 |                                    |                    |                               |                |  |            |   |                                   |  |                 |                                    |       |                                    |            |   |
| (3) +105℃                         | 30±2 Minutes                               |  |                 |                                    |                    |                               |                |  |            |   |                                   |  |                 |                                    |       |                                    |            |   |
| (1) to (3)=1 cycle, total 5 cycle |  |  |                 |                                    |                    |                               |                |  |            |   |                                   |  |                 |                                    |       |                                    |            |   |
| Leakage current                   | Not more than the specified value.         |  |                 |                                    |                    |                               |                |  |            |   |                                   |  |                 |                                    |       |                                    |            |   |
| tan δ                             | Not more than the specified value.         |  |                 |                                    |                    |                               |                |  |            |   |                                   |  |                 |                                    |       |                                    |            |   |
| Appearance                        | There shall be no leakage of electrolyte.  |  |                 |                                    |                    |                               |                |  |            |   |                                   |  |                 |                                    |       |                                    |            |   |
| 4.14                              | Damp heat test                             | <p>&lt;Condition&gt;<br/>Humidity test:<br/>According to IEC60384-4 No.4.12 methods, capacitor shall be exposed for 500±8 hours in an atmosphere of 90~95%R H .at 40±2℃, the characteristic change shall meet the following requirement.</p> <p>&lt;Criteria&gt;</p> <table><tr><td>Leakage current</td><td>Not more than the specified value.</td></tr><tr><td>Capacitance Change</td><td>Within ±20% of initial value.</td></tr><tr><td>tan δ</td><td>Not more than 120% of the specified value.</td></tr><tr><td>Appearance</td><td>There shall be no leakage of electrolyte.</td></tr></table>   | Leakage current | Not more than the specified value. | Capacitance Change | Within ±20% of initial value. | tan δ          | Not more than 120% of the specified value. | Appearance | There shall be no leakage of electrolyte. |                                   |  |                 |                                    |       |                                    |            |   |
| Leakage current                   | Not more than the specified value.         |  |                 |                                    |                    |                               |                |  |            |   |                                   |  |                 |                                    |       |                                    |            |   |
| Capacitance Change                | Within ±20% of initial value.              |  |                 |                                    |                    |                               |                |  |            |   |                                   |  |                 |                                    |       |                                    |            |   |
| tan δ                             | Not more than 120% of the specified value. |  |                 |                                    |                    |                               |                |  |            |   |                                   |  |                 |                                    |       |                                    |            |   |
| Appearance                        | There shall be no leakage of electrolyte.  |  |                 |                                    |                    |                               |                |  |            |   |                                   |  |                 |                                    |       |                                    |            |   |
| 4.15                              | Vent test                                  | <p>&lt;Condition&gt;<br/>The following test only apply to those products with vent.<br/>D.C. test<br/>The capacitor is connected with its polarity reversed to a DC power source. Then a current selected from Table 2 is applied.</p> <p>&lt;Table 2&gt;</p> <table><tr><td>Diameter (mm)</td><td>DC Current (A)</td></tr><tr><td>22.4 or less</td><td>10</td></tr></table> <p>&lt;Criteria&gt;<br/>The vent shall operate with no dangerous conditions such as flames or dispersion of pieces of the capacitor and/or case.</p>  | Diameter (mm)   | DC Current (A)                     | 22.4 or less       | 10                            |                |  |            |   |                                   |  |                 |                                    |       |                                    |            |   |
| Diameter (mm)                     | DC Current (A)                             |  |                 |                                    |                    |                               |                |  |            |   |                                   |  |                 |                                    |       |                                    |            |   |
| 22.4 or less                      | 10   |  |                 |                                    |                    |                               |                |  |            |   |                                   |  |                 |                                    |       |                                    |            |   |

4.16

Maximum permissible (ripple current, temperature coefficient)

**<Condition>**  
The maximum permissible ripple current is the maximum A.C current at 120Hz and can be applied at maximum operating temperature  
Table-3  
The combined value of D.C voltage and the peak A.C voltage shall not exceed the rated voltage and shall not reverse voltage.


Frequency multipliers:

| Coefficient<br>Voltage (V) | Freq.<br>(Hz) | 60   | 120  | 1k   | 10~50k |
|----------------------------|---------------|------|------|------|--------|
| 10~100V                    |               | 0.90 | 1.00 | 1.15 | 1.25   |
| 160~250V                   |               | 0.80 | 1.00 | 1.15 | 1.47   |
| 315~500V                   |               | 0.80 | 1.00 | 1.15 | 1.47   |


Temperature coefficient:

| Temperature (°C) | 65   | 85   | 95   | 105  |
|------------------|------|------|------|------|
| Factor           | 2.23 | 1.73 | 1.41 | 1.00 |

5. Product printing diagram and terminal size diagram:



SW



SZ




Table-3

## 体积和最大纹波电流 CASE SIZE & MAX RIPPLE CURRENT

Size φDXL (mm) , Maximum Permissible Ripple Current at 105°C 120Hz

| Voltage    |      | 10V(1A)   |                | 16V(1C)   |                | 25V(1E)   |                | 35V(1V)   |                |
|------------|------|-----------|----------------|-----------|----------------|-----------|----------------|-----------|----------------|
| Cap.( μ F) | Code | Case Size | Ripple Current | Case Size | Ripple Current | Case Size | Ripple Current | Case Size | Ripple Current |
| 2200       | 228  |           |                |           |                |           |                | 22x25     | 1.10           |
| 3300       | 338  |           |                |           |                |           |                | 22x30     | 1.42           |
|            |      |           |                |           |                |           |                | 25x25     | 1.41           |
| 3900       | 398  |           |                |           |                | 22x25     | 1.31           | 22x35     | 1.58           |
|            |      |           |                |           |                |           |                | 25x30     | 1.58           |
| 4700       | 478  |           |                |           |                | 22x30     | 1.51           | 22x40     | 1.78           |
|            |      |           |                |           |                | 25x25     | 1.51           | 30x25     | 1.77           |
| 5600       | 568  |           |                | 22x25     | 1.44           | 22x35     | 1.70           | 25x35     | 1.98           |
|            |      |           |                |           |                |           |                | 30x30     | 1.98           |
|            |      |           |                |           |                |           |                | 35x25     | 2.03           |
| 6800       | 688  | 22x25     | 1.30           | 22x30     | 1.66           | 22x40     | 1.92           | 22x50     | 2.26           |
|            |      |           |                | 25x25     | 1.66           | 25x30     | 1.87           | 25x40     | 2.24           |
|            |      |           |                |           |                | 30x25     | 1.90           |           |                |
| 8200       | 828  |           |                | 22x35     | 1.87           | 25x35     | 2.14           | 25x50     | 2.57           |
|            |      |           |                |           |                | 30x30     | 2.15           | 30x35     | 2.50           |
|            |      |           |                |           |                | 35x25     | 2.19           | 35x30     | 2.55           |
| 10000      | 109  | 22x30     | 1.65           | 22x40     | 2.12           | 22x50     | 2.45           | 30x40     | 2.86           |
|            |      | 25x25     | 1.64           | 25x30     | 2.07           | 25x40     | 2.43           | 35x35     | 2.88           |
|            |      |           |                | 30x25     | 2.11           |           |                |           |                |
| 12000      | 129  | 25x35     | 1.85           | 25x35     | 2.37           | 25x50     | 2.78           | 30x50     | 3.32           |
|            |      | 25x30     | 1.85           | 30x30     | 2.37           | 30x35     | 2.70           | 35x40     | 3.30           |
|            |      | 30x25     | 1.89           | 35x25     | 2.42           | 35x30     | 2.76           |           |                |
| 15000      | 159  | 22x40     | 2.12           | 22x50     | 2.74           | 30x40     | 3.13           | 35x45     | 3.85           |
|            |      | 25x35     | 2.16           | 25x40     | 2.71           | 35x35     | 3.16           |           |                |
| 18000      | 189  | 22x50     | 2.45           | 25x50     | 3.11           | 30x50     | 3.64           | 35x50     | 4.29           |
|            |      | 25x40     | 2.43           | 30x35     | 3.02           |           |                |           |                |
|            |      | 30x30     | 2.37           | 35x30     | 3.09           | 35x40     | 3.61           |           |                |
|            |      | 35x25     | 2.42           |           |                |           |                |           |                |
| 22000      | 229  | 30x35     | 2.73           | 30x40     | 3.46           |           |                |           |                |
|            |      | 35x30     | 2.79           | 35x35     | 3.49           |           |                |           |                |
| 27000      | 279  | 25x50     | 3.11           | 30x50     | 4.07           | 35x50     | 4.70           |           |                |
|            |      | 30x40     | 3.13           | 35x40     | 4.04           |           |                |           |                |
| 33000      | 339  | 30x35     | 3.49           |           |                |           |                |           |                |
| 39000      | 399  | 30x50     | 3.99           | 35x50     | 5.16           |           |                |           |                |
|            |      | 35x40     | 3.96           |           |                |           |                |           |                |
| 47000      | 479  | 35x50     | 4.62           |           |                |           |                |           |                |

## 体积和最大纹波电流 CASE SIZE & MAX RIPPLE CURRENT

Size φDXL (mm) , Maximum Permissible Ripple Current at 105°C 120Hz

| Voltage    |      | 50V(1H)   |                | 63V(1J)   |                | 80V(1K)   |                | 100V(2A)  |                |
|------------|------|-----------|----------------|-----------|----------------|-----------|----------------|-----------|----------------|
| Cap.( μ F) | Code | Case Size | Ripple Current | Case Size | Ripple Current | Case Size | Ripple Current | Case Size | Ripple Current |
| 390        | 397  |           |                |           |                |           |                | 22x25     | 0.78           |
| 560        | 567  |           |                |           |                |           |                | 22x30     | 0.99           |
|            |      |           |                |           |                |           |                | 25x25     | 0.98           |
| 680        | 687  |           |                |           |                | 22x25     | 0.97           | 22x35     | 1.12           |
| 820        | 827  |           |                |           |                | 22x30     | 1.12           | 22x40     | 1.26           |
|            |      |           |                |           |                |           |                | 25x30     | 1.23           |
|            |      |           |                |           |                |           |                | 30x25     | 1.25           |
| 1000       | 108  |           |                | 22x25     | 1.00           | 22x35     | 1.70           | 25x35     | 1.41           |
|            |      |           |                |           |                | 25x25     | 1.92           | 30x30     | 1.42           |
|            |      |           |                |           |                |           |                | 35x25     | 1.54           |
| 1200       | 128  |           |                | 22x30     | 1.15           | 22x40     | 1.42           | 22x50     | 1.60           |
|            |      |           |                | 25x25     | 1.15           | 25x30     | 1.39           | 25x40     | 1.59           |
|            |      |           |                |           |                | 30x25     | 1.41           | 30x35     | 1.61           |
| 1500       | 158  | 22x25     | 1.02           | 22x35     | 1.32           | 25x35     | 1.62           | 25x50     | 1.86           |
|            |      |           |                |           |                |           |                | 30x40     | 1.87           |
|            |      |           |                |           |                |           |                | 35x30     | 1.85           |
| 1800       | 188  | 22x30     | 1.17           | 22x40     | 1.49           | 22x50     | 1.84           | 35x35     | 2.07           |
|            |      |           |                | 25x30     | 1.45           | 25x40     | 1.82           |           |                |
|            |      | 25x25     | 1.17           | 30x25     | 1.48           | 30x30     | 1.78           |           |                |
|            |      |           |                |           |                | 35x25     | 1.82           |           |                |
| 2200       | 228  | 22x35     | 1.33           | 25x35     | 1.67           | 25x50     | 2.11           | 30x50     | 2.40           |
|            |      |           |                | 30x30     | 1.68           | 30x35     | 2.05           | 35x40     | 2.39           |
|            |      |           |                | 35x25     | 1.71           | 35x30     | 2.09           |           |                |
| 2700       | 278  | 22x40     | 1.51           | 22x50     | 1.92           | 30x40     | 2.35           | 35x50     | 2.81           |
|            |      | 25x30     | 1.47           | 25x40     | 1.90           | 35x35     | 2.37           |           |                |
|            |      | 30x25     | 1.50           | 30x35     | 1.93           |           |                |           |                |
| 3300       | 338  | 25x35     | 1.70           | 25x50     | 2.20           | 30x50     | 2.75           |           |                |
|            |      | 30x30     | 1.70           | 35x30     | 2.18           | 35x40     | 2.73           |           |                |
|            |      | 35x25     | 1.74           |           |                |           |                |           |                |
| 3900       | 398  | 22x50     | 1.91           | 30x40     | 2.41           |           |                |           |                |
|            |      | 25x40     | 1.89           | 35x35     | 2.43           |           |                |           |                |
| 4700       | 478  | 30x35     | 2.11           | 30x50     | 2.80           | 35x50     | 3.46           |           |                |
|            |      | 35x30     | 2.16           | 35x40     | 2.78           |           |                |           |                |
| 5600       | 568  | 25x50     | 2.38           |           |                |           |                |           |                |
|            |      | 30x40     | 2.39           |           |                |           |                |           |                |
|            |      | 35x35     | 2.41           |           |                |           |                |           |                |
| 6800       | 688  | 30x50     | 2.79           | 35x50     | 3.55           |           |                |           |                |
|            |      | 35x40     | 2.78           |           |                |           |                |           |                |
| 10000      | 109  | 35x50     | 3.57           |           |                |           |                |           |                |

## 体积和最大纹波电流 CASE SIZE & MAX RIPPLE CURRENT

Size φDXL (mm) , Maximum Permissible Ripple Current at 105°C 120Hz

| Voltage    |      | 160V(2C)  |                | 200V(2D)  |                | 250V(2E)  |                | 315V(2R)  |                |
|------------|------|-----------|----------------|-----------|----------------|-----------|----------------|-----------|----------------|
| Cap.( μ F) | Code | Case Size | Ripple Current | Case Size | Ripple Current | Case Size | Ripple Current | Case Size | Ripple Current |
| 150        | 157  |           |                |           |                |           |                | 22x30     | 0.86           |
| 180        | 187  |           |                |           |                |           |                | 22x35     | 0.98           |
|            |      |           |                |           |                |           |                | 25x30     | 1.01           |
| 220        | 227  |           |                |           |                | 22x30     | 1.09           | 22x40     | 1.10           |
|            |      |           |                |           |                |           |                | 30x25     | 1.17           |
| 270        | 277  |           |                | 22x25     | 1.10           | 22x35     | 1.28           | 22x45     | 1.24           |
|            |      |           |                |           |                |           |                | 25x35     | 1.27           |
| 330        | 337  |           |                |           |                | 25x30     | 1.42           | 22x50     | 1.39           |
|            |      |           |                |           |                |           |                | 25x40     | 1.45           |
|            |      |           |                |           |                |           |                | 30x30     | 1.40           |
| 390        | 397  | 22x30     | 1.42           | 22x35     | 1.47           | 22x45     | 1.61           | 25x45     | 1.60           |
|            |      |           |                | 25x30     | 1.50           | 25x35     | 1.53           |           |                |
|            |      |           |                |           |                | 30x30     | 1.62           |           |                |
| 470        | 477  |           |                | 22x40     | 1.64           | 22x50     | 1.79           | 25x50     | 1.78           |
|            |      |           |                |           |                |           |                | 30x40     | 1.81           |
|            |      |           |                |           |                |           |                | 35x30     | 1.82           |
| 560        | 567  | 22x35     | 1.77           | 22x45     | 1.82           | 25x45     | 1.98           | 30x45     | 2.02           |
|            |      | 25x30     | 1.81           | 25x35     | 1.82           | 30x35     | 1.95           | 35x35     | 2.00           |
|            |      |           |                | 30x25     | 1.78           |           |                |           |                |
| 680        | 687  | 22x40     | 1.98           | 22x50     | 1.90           | 25x50     | 2.21           | 30x50     | 2.21           |
|            |      | 25x35     | 2.01           | 25x40     | 1.98           | 30x40     | 2.18           | 35x40     | 2.29           |
|            |      | 30x25     | 1.96           | 30x30     | 1.98           | 35x30     | 2.15           |           |                |
| 820        | 827  | 22x45     | 2.20           | 25x45     | 2.20           | 30x45     | 2.45           | 35x45     | 2.57           |
|            |      |           |                | 30x35     | 2.22           | 35x35     | 2.38           |           |                |
| 1000       | 108  | 25x45     | 2.65           | 25x50     | 2.46           | 30x50     | 2.68           | 35x50     | 2.89           |
|            |      | 30x35     | 2.55           | 30x40     | 2.53           | 35x40     | 2.72           |           |                |
|            |      | 35x25     | 2.55           | 35x35     | 2.77           |           |                |           |                |
| 1200       | 128  | 25x50     | 2.93           | 30x45     | 2.84           | 35x45     | 3.05           |           |                |
|            |      | 30x40     | 2.84           | 35x35     | 2.88           |           |                |           |                |
|            |      | 35x30     | 2.86           |           |                |           |                |           |                |
| 1500       | 158  | 30x45     | 3.17           | 35x40     | 3.34           | 35x45     | 3.20           |           |                |
|            |      | 35x35     | 3.22           |           |                | 35x50     | 3.49           |           |                |
| 1800       | 188  | 30x50     | 3.53           | 35x45     | 3.74           |           |                |           |                |
|            |      | 35x40     | 3.66           |           |                |           |                |           |                |
| 2200       | 228  | 35x45     | 4.14           |           |                |           |                |           |                |
| 2700       | 278  | 35x50     | 4.68           |           |                |           |                |           |                |

体积和最大纹波电流 CASE SIZE & MAX RIPPLE CURRENT

Size  $\phi$ DXL (mm) , Maximum Permissible Ripple Current at 105°C 120Hz

| Voltage    |      | 350V(2V)  |                | 400V(2G)  |                | 420V(2M)  |                | 450V(2W)  |                |
|------------|------|-----------|----------------|-----------|----------------|-----------|----------------|-----------|----------------|
| Cap.( μ F) | Code | Case Size | Ripple Current | Case Size | Ripple Current | Case Size | Ripple Current | Case Size | Ripple Current |
| 82         | 826  |           |                |           |                |           |                | 22x30     | 0.64           |
| 100        | 107  |           |                | 22x30     | 0.71           | 22x30     | 0.71           | 22x35     | 0.74           |
|            |      |           |                |           |                |           |                | 25x30     | 0.75           |
| 120        | 127  | 22x30     | 0.78           | 22x35     | 0.80           | 22x35     | 0.80           | 22x40     | 0.82           |
|            |      |           |                |           |                | 25x30     | 0.73           |           |                |
| 150        | 157  | 22x35     | 0.90           | 22x40     | 0.91           | 22x40     | 0.91           | 22x45     | 0.93           |
|            |      |           |                | 25x35     | 0.99           |           |                | 25x35     | 0.94           |
|            |      |           |                |           |                |           |                | 30x30     | 1.00           |
| 180        | 187  | 25x30     | 1.01           | 22x45     | 1.01           | 22x45     | 1.01           | 22x50     | 1.01           |
|            |      |           |                | 25x35     | 1.03           | 25x40     | 1.10           | 25x40     | 1.03           |
|            |      |           |                | 30x30     | 1.10           | 30x30     | 1.10           | 30x30     | 1.03           |
| 220        | 227  | 22x45     | 1.16           | 22x50     | 1.14           | 25x45     | 1.20           | 25x45     | 1.16           |
|            |      | 25x35     | 1.14           | 25x40     | 1.19           | 30x35     | 1.21           | 30x35     | 1.17           |
|            |      | 30x30     | 1.21           |           |                | 35x25     | 1.22           | 35x30     | 1.24           |
| 270        | 277  | 22x50     | 1.26           | 25x50     | 1.39           | 25x50     | 1.35           | 25x50     | 1.31           |
|            |      | 25x40     | 1.31           | 30x35     | 1.35           | 30x40     | 1.37           | 30x40     | 1.33           |
|            |      | 30x30     | 1.27           |           |                | 35x30     | 1.38           | 35x35     | 1.39           |
| 330        | 337  | 25x45     | 1.46           | 30x45     | 1.59           | 30x45     | 1.50           | 30x50     | 1.58           |
|            |      | 30x35     | 1.43           | 35x30     | 1.52           | 35x35     | 1.54           |           |                |
| 390        | 397  | 25x50     | 1.62           | 30x45     | 1.68           | 30x50     | 1.72           | 35x40     | 1.73           |
|            |      | 30x40     | 1.60           | 35x35     | 1.67           | 35x40     | 1.73           |           |                |
|            |      | 35x35     | 1.76           |           |                |           |                |           |                |
| 470        | 477  | 30x45     | 1.81           | 30x50     | 1.89           | 35x45     | 1.94           | 35x50     | 1.98           |
|            |      | 35x35     | 1.83           | 35x40     | 1.90           |           |                |           |                |
| 560        | 567  | 30x50     | 2.00           | 35x45     | 2.12           | 35x50     | 2.17           | 35x50     | 2.0            |
|            |      | 35x40     | 2.07           |           |                |           |                |           |                |
| 680        | 687  | 35x45     | 2.34           | 35x50     | 2.39           |           |                |           |                |
| 820        | 827  | 35x50     | 2.62           |           |                |           |                |           |                |

Remark:

The sizes in the above table are all general specifications. If you need other specifications, please contact us.



**Attachment: Application Guidelines****1.Circuit Design****1.1 Operating Temperature and Frequency**

Electrolytic capacitor electrical parameters are normally specified at 20 °C temperature and 120Hz frequency. These parameters vary with changes in temperature and frequency. Circuit designers should take these changes into consideration.

**(1) Effects of operating temperature on electrical parameters**

- a) At higher temperatures, leakage current and capacitance increase while equivalent series resistance (ESR) decreases.
- b) At lower temperatures, leakage current and capacitance decrease while equivalent series resistance (ESR) increases.

**(2) Effects of frequency on electrical parameters**

- a) At higher frequencies capacitance and impedance decrease while  $\tan \delta$  increases.
- b) At lower frequencies, ripple current generated heat will rise due to an increase in equivalent series resistance (ESR).

**1.2 Operating Temperature and Life Expectancy**

See the file: Life calculation of aluminum electrolytic capacitor

**1.3 Common Application Conditions to Avoid**

The following misapplication load conditions will cause rapid deterioration to capacitor electrical parameters. In addition, rapid heating and gas generation within the capacitor can occur causing the pressure relief vent to operate and resultant leakage of electrolyte. Under Leaking electrolyte is combustible and electrically conductive.

**(1) Reverse Voltage**

DC capacitors have polarity. Verify correct polarity before insertion. For circuits with changing or uncertain polarity, use DC bipolar capacitors. DC bipolar capacitors are not suitable for use in AC circuits.

**(2) Charge / Discharge Applications**

Standard capacitors are not suitable for use in repeating charge / discharge applications. For charge / discharge applications consult us and advise actual conditions.

**(3) Over voltage**

Do not apply voltages exceeding the maximum specified rated voltage. Voltages up to the surge voltage rating are acceptable for short periods of time. Ensure that the sum of the DC voltage and the superimposed AC ripple voltage does not exceed the rated voltage.

#### (4) Ripple Current

Do not apply ripple currents exceeding the maximum specified value. For high ripple current applications, use a capacitor designed for high ripple currents or contact us with your requirements.

Ensure that allowable ripple currents superimposed on low DC bias voltages do not cause reverse voltage conditions.

#### 1.4 Using Two or More Capacitors in Series or Parallel

##### (1) Capacitors Connected in Parallel

The circuit resistance can closely approximate the series resistance of the capacitor causing an imbalance of ripple current loads within the capacitors. Careful design of wiring methods can minimize the possibility of excessive ripple currents applied to a capacitor.

##### (2) Capacitors Connected in Series

Normal DC leakage current differences among capacitors can cause voltage imbalances. The use of voltage divider shunt resistors with consideration to leakage current can prevent capacitor voltage imbalances.

#### 1.5 Capacitor Mounting Considerations

##### (1) Double Sided Circuit Boards

Avoid wiring pattern runs, which pass between the mounted capacitor and the circuit board.

When dipping into a solder bath, excess solder may collect under the capacitor by capillary action and short circuit the anode and cathode terminals.

##### (2) Circuit Board Hole Positioning

The vinyl sleeve of the capacitor can be damaged if solder passes through a lead hole for subsequently processed parts. Special care when locating hole positions in proximity to capacitors is recommended.

##### (3) Circuit Board Hole Spacing

The circuit board holes spacing should match the capacitor lead wire spacing within the specified tolerances. Incorrect spacing can cause excessive lead wire stress during the insertion process. This may result in premature capacitor failure due to short or open circuit, increased leakage current, or electrolyte leakage.

##### (4) Clearance for Case Mounted Pressure Relief vents

Capacitors with case mounted pressure relief vents require sufficient clearance to allow for proper vent operation. The minimum clearances are dependent on capacitor diameters as proper vent operation. The minimum clearances are dependent on capacitor diameters as follows.

$\phi 6.3 \sim \phi 16\text{mm}$ : 2mm minimum,  $\phi 18 \sim \phi 35\text{mm}$ : 3mm minimum,  $\phi 40\text{mm}$  or greater: 5mm minimum.

##### (5) Clearance for Seal Mounted Pressure Relief Vents

A hole in the circuit board directly under the seal vent location is required to allow proper release of pressure.

##### (6) Wiring Near the Pressure Relief Vent

Avoid locating high voltage or high current wiring or circuit board paths above the pressure relief vent.

Flammable, high temperature gas exceeding  $100^{\circ}\text{C}$  may be released which could dissolve the wire insulation and ignite.

(7) Circuit Board patterns Under the Capacitor

Avoid circuit board runs under the capacitor as electrolyte leakage could cause an electrical short.

(8) Screw Terminal Capacitor Mounting

Do not orient the capacitor with the screw terminal side of the capacitor facing downwards.

Tighten the terminal and mounting bracket screws within the torque range specified in the specification.

1.6 Electrical Isolation of the Capacitor

Completely isolate the capacitor as follows.

- (1) Between the cathode and the case (except for axially leaded B types) and between the anode terminal and other circuit paths
- (3) Between the extra mounting terminals (on T types) and the anode terminal, cathode terminal, and other circuit paths.

1.7 The Product characteristic should take the sample as the standard.

1.8 If conduct the load or shelf life test, must be collect date code within 6 months products of sampling.

1.9 Capacitor Sleeve

The vinyl sleeve or laminate coating is intended for marking and identification purposes and is not meant to electrically insulate the capacitor.

The sleeve may split or crack if immersed into solvents such as toluene or xylene, and then exposed to high temperatures.

**CAUTION!**

Always consider safety when designing equipment and circuits. Plan for worst case failure modes such as short circuits and open circuits which could occur during use.

- (1) Provide protection circuits and protection devices to allow safe failure modes.
- (2) Design redundant or secondary circuits where possible to assure continued operation in case of main circuit failure.

## 2.Capacitor Handling Techniques

### 2.1 Considerations Before Using

- (1) Capacitors have a finite life. Do not reuse or recycle capacitors from used equipment.
- (2) Transient recovery voltage may be generated in the capacitor due to dielectric absorption. If required, this voltage can be discharged with a resistor with a value of about  $1k\ \Omega$ .
- (3) Capacitors stored for long periods of time may exhibit an increase in leakage current. This can be corrected by gradually applying rated voltage in series with a resistor of approximately  $1k\ \Omega$ .
- (4) If capacitors are dropped, they can be damaged mechanically or electrically. Avoid using dropped capacitors.
- (5) Dented or crushed capacitors should not be used. The seal integrity can be compromised and loss of electrolyte / shortened life can result.

### 2.2 Capacitor Insertion

- \* (1) Verify the correct capacitance and rated voltage of the capacitor.
- \* (2) Verify the correct polarity of the capacitor before inserting.
- \* (3) Verify the correct hole spacing before insertion (land pattern size on chip type) to avoid stress on the terminals.
- (4) Ensure that the auto insertion equipment lead clinching operation does not stress the capacitor leads where they enter the seal of the capacitor.

For chip type capacitors, excessive mounting pressure can cause high leakage current, short circuit, or disconnection.

### 2.3 Manual Soldering

- (1) Observe temperature and time soldering specifications or do not exceed temperatures of  $400\ ^\circ\text{C}$  for 3 seconds or less.
- (2) If lead wires must be formed to meet terminal board hole spacing, avoid stress on the lead wire where it enters the capacitor seal.
- (3) If a soldered capacitor must be removed and reinserted, avoid excessive stress to the capacitor leads.
- (4) Avoid touching the tip of the soldering iron to the capacitor, to prevent melting of the vinyl sleeve.

### 2.4 Flow Soldering

- (1) Do not immerse the capacitor body into the solder bath as excessive internal pressure could result.
- (2) Observe proper soldering conditions (temperature, time, etc.) Do not exceed the specified limits.
- (3) Do not allow other parts or components to touch the capacitor during soldering.

### 2.5 Other Soldering Considerations

Rapid temperature rises during the preheat operation and resin bonding operation can cause cracking of the capacitor vinyl sleeve.

For heat curing, do not exceed  $150^\circ\text{C}$  for a maximum time of 2 minutes.

## 2.6 Capacitor Handling after Solder

- (1). Avoid movement of the capacitor after soldering to prevent excessive stress on the lead wires where they enter the seal.
- (2). Do not use capacitor as a handle when moving the circuit board assembly.
- (3). Avoid striking the capacitor after assembly to prevent failure due to excessive shock.

## 2.7 Circuit Board Cleaning

- \* (1 ) Circuit boards can be immersed or ultrasonically cleaned using suitable cleaning solvents for up to 5 minutes and up to 60°C maximum temperatures. The boards should be thoroughly rinsed and dried. The use of ozone depleting cleaning agents is not recommended in the interest of protecting the environment.
- \* (2) Avoid using the following solvent groups unless specifically allowed for in the specification;
  - Halogenated cleaning solvents: except for solvent resistant capacitor types, halogenated solvents can permeate the seal and cause internal capacitor corrosion and failure. For solvent resistant capacitors, carefully follow the temperature and time requirements of the specification. 1-1-1 trichloroethane should never be used on any aluminum electrolytic capacitor.
  - Alkali solvents : could attack and dissolve the aluminum case.
  - Petroleum based solvents: deterioration of the rubber seal could result.
  - Xylene : deterioration of the rubber seal could result.
  - Acetone : removal of the ink markings on the vinyl sleeve could result.
- \* (3 ) A thorough drying after cleaning is required to remove residual cleaning solvents which may be trapped between the capacitor and the circuit board. Avoid drying temperatures, which exceed the maximum rated temperature of the capacitor.
- \* (4) Monitor the contamination levels of the cleaning solvents during use by electrical conductivity, pH, specific gravity, or water content. Chlorine levels can rise with contamination and adversely affect the performance of the capacitor.

Please consult us for additional information about acceptable cleaning solvents or cleaning methods.

## 2.8 Mounting Adhesives and Coating Agents

When using mounting adhesives or coating agents to control humidity, avoid using materials containing halogenated solvents. Also, avoid the use of chloroprene based polymers.

After applying adhesives or coatings, dry thoroughly to prevent residual solvents from being trapped between the capacitor and the circuit board.

## 3. Precautions for using capacitors

### 3.1 Environmental Conditions

Capacitors should not be stored or used in the following environments.

- \* (1) Temperature exposure above the maximum rated or below the minimum rated temperature of the capacitor.
- \* (2) Direct contact with water, salt water, or oil.
- \* (3) High humidity conditions where water could condense on the capacitor.

- \* (4) Exposure to toxic gases such as hydrogen sulfide, sulfuric acid, nitric acid chlorine, or ammonia.
- \* (5) Exposure to ozone, radiation, or ultraviolet rays.
- \* (6) Vibration and shock conditions exceeding specified requirements.

### 3.2 Electrical Precautions

- (1) Avoid touching the terminals of the capacitor as possible electric shock could result. The exposed aluminum case is not insulated and could also cause electric shock if touched.
- (2) Avoid short circuit the area between the capacitor terminals with conductive materials including liquids such as acids or alkaline solutions.

## 4. Emergency Procedures

- (1) If the pressure relief vent of the capacitor operates, immediately turn off the equipment and disconnect from the power source. This will minimize additional damage caused by the vaporizing electrolyte.
- (2) Avoid contact with the escaping electrolyte gas which can exceed 100°C temperatures.  
If electrolyte or gas enters the eye, immediately flush the eyes with large amounts of water.  
If electrolyte or gas is ingested by mouth, gargle with water.  
If electrolyte contacts the skin, wash with soap and water.

## 5. Long Term Storage

Leakage current of a capacitor increases with long storage times. The aluminum oxide film deteriorates as a function of temperature and time. If used without reconditioning, an abnormally high current will be required to restore the oxide film. This current surge could cause the circuit or the capacitor to fail.

After one year, a capacitor should be reconditioned by applying rated voltage in series with a 1000  $\Omega$  current limiting resistor for a time period of 30 minutes.

If the expired date of products date code is over eighteen months, the products should be return to confirmation.

### 5.1 Environmental Conditions

The capacitor shall be not use in the following condition:

- (1) Temperature exposure above the maximum rated or below the minimum rated temperature of the capacitor.
- (2) Direct contact with water, salt water, or oil.
- (3) High humidity conditions where water could condense on the capacitor.
- (4) Exposure to toxic gases such as hydrogen sulfide, sulfuric acid, nitric acid, chlorine, or ammonia.
- (5) Exposure to ozone, radiation, or ultraviolet rays.
- (6) Vibration and shock conditions exceeding specified requirements.

## 6. Capacitor Disposal

When disposing of capacitors, use one of the following methods.

- \* Incinerate after crushing the capacitor or puncturing the can wall (to prevent explosion due to internal pressure rise). Capacitors should be incinerated at high temperatures to prevent the release of toxic gases such as chlorine from the polyvinyl chloride sleeve, etc.
- \* Dispose of as solid waste.

NOTE: Local laws may have specific disposal requirements, which must be followed.